

# M754 (75HP)

**EuroV**  
New European emission standards

# LOVOL



## PRODUCT FEATURES

LOVOL M754 is designed for comfort and easy operation. Cabin with A/C allows the operator has an excellent view and comfortable environment, operation handles with ergonomic design make the drive easy and flexible. The strong powertrain enable M754 can meet with utility jobs, transportation, and farming jobs.



## WEICHAI LOVOL HEAVY INDUSTRY CO., LTD.

Add: No.192 S Beihai Road, Weifang, Shandong, China. PC: 261206 Tel: +86-536-7527358  
Website: [www.lovolglobal.com](http://www.lovolglobal.com) E-mail: [lovol\\_agriexport@global.lovol.com](mailto:lovol_agriexport@global.lovol.com)




## PRODUCTS INFORMATION




- A Cabin with A/C and a Grammer seat give you a new feeling, while the curve glass and 4 pillar design ensure a panoramic view in all directions.
- A tilt steering column lets you easy to go in and out, and keep you a natural position for your arms.
- Max. speed about 38.2 km/h, high efficiency for transportation;
- Donaldson dry type air filter will be easy for the maintenance and save your cost;
- Adjustable towing bar, more convenient to link with varieties implements;
- Equipped with dual circuit braking system, more secure for transportation.
- A 60L fuel tank decreases the downtime as much as possible, gives a high productivity working day;
- 41 L/m hydraulic flow and 1400KG lift ability provides a wide range of implements.
- Electronic control 4WD and PTO, make the operation easy and comfortable.



Euro V Doosan engine



12+12 shuttle gears



Panatery structure



Full view cabin with A/C

## PRODUCT PARAMETER



Model		M754
ENGINE		
TYPE		DOOSAN D24
DISPLACEMENT(L)/CYLINDERS/ASPIRATION		2.392/4/T
MAX.POWER	(HP/KW)	75/55.1
RATED SPEED	(RPM)	2400
TRANSMISSION		
DRIVE TYPE		4 WD
*GEARS		Synchromesh 12F+12R
PTO		540/1000 Electronic Control
BRAKE		Oil immersed disc brake
DIMENSION & WEIGHT WITH STANDARD TIRES		
OVERALL SIZE (Length×width×height)	(MM)	4105×1830×2910(To Cab) /2678 (To ROPS)
WHEELBASE	(MM)	2070
MAX.FRONT/REAR BALLAST	(KG)	150/540
STRUCTURE WEIGHT	(KG)	2765(Cab)/2605(ROPS)
FRONT TYRES		300/70R20
REAR TYRES		380/85R30
FRONT TRACK	(MM)	1480
REAR TRACK	(MM)	1410

\*synchronizer type for main gears

Due to real-time changes involving product batches, production and supply factors, in order to provide accurate product information, specifications, and features, LOVOL may make real-time adjustments to text descriptions and images in the brochure, so that they match the product performance, specifications, indexes, and components of the actual product. Product information is subject to such changes and adjustments without notice.